

	ProZone ProC332JPW	Honeywell HZ432	ZoneFirst MDP3	The ProZone Difference
Zones on Panel	3	4	3	<ul style="list-style-type: none"> Compatible with Gas/Electric, Conventional Heat Pump and Dual Fuel Heat Pump equipment. Equipment selected using the digital display on the panel. Expandable to 6 zones using the ProC300JX in the same case. Competition adder panels are in separate cases. Three stages of heating and two stages of cooling. Plug and play dampers eliminate the time and errors associated with traditional wiring. Not offered by Honeywell. Display module on panel walks the installer through installation, tests the installation, saves panel configurations for cloning multiple panels and sets advanced options. Competition doesn't offer cloning option. Adjustable heating / cooling discharge air temperature limits using digital display Built-in fresh air controller meeting ASHRAE 62-2. Includes fresh air damper connector on panel. Competition requires purchasing external fresh air controller and does not include a connector on the panel. Wireless thermostat communication built into the panel. All LED indicators are visible with panel cover on.
Expandable	Yes, to 6 zones in same case.	Yes. Separate cases.	Yes. Separate cases.	
Compatible Equipment				
Gas/Electric	Yes.	Yes.	Yes.	
Conventional Heat Pump	Yes.	Yes.	Yes.	
Dual Fuel Heat Pump	Yes.	Yes.	Yes.	
Equipment Selection	Set using digital display.	Set using digital display.	Set using digital display.	
Heating Stages	Three.	Three.	Three.	
Cooling Stages	Two.	Two.	Two.	
Damper Wiring	Plug and Play	Wired	Plug and Play	
Damper Construction	Damper uses foam gasket between dual blades with efficient airflow.	Uses 1/2-inch foam gasket attached to sleeve. Reduces effective damper diameter by 1 inch.	Uses 1/2-inch foam gasket attached to sleeve. Reduces effective damper diameter by 1 inch.	
Damper Actuator Type	Power Open/Close.	Spring Return.	Power Open/Close.	
Damper Actuator VA	2.4VA Operating .7VA Holding	7VA	2.4VA Operating .7VA Holding	
Digital Display for changing options, monitoring installation and cloning.	Yes. Clone multiple panels using the PDMi3, provided at no cost to installers.	Yes. No cloning option.	Yes. No cloning option.	
Adjustable heating / cooling discharge air temperature limits.	Yes.	Yes.	Yes.	
Built-in fresh air controller to meet ASHRAE 62-2 and Title24.	Yes. Includes a connector for the fresh air damper.	No. Requires an external fresh air controller.	No. Requires an external fresh air controller.	
Fresh Air Damper Connector.	Yes.	No.	No.	
Zone1 Thermostats.	Heat/Cool or Heat Pump.	Heat/Cool or Heat Pump.	Heat/Cool or Heat Pump.	
Zone2 and 3 Thermostats.	Heat/Cool.	Heat/Cool or Heat Pump.	Heat/Cool or Heat Pump.	
Wireless Thermostats.	Yes. Built into the panel. Wireless or wired thermostats.	Yes. Requires wireless adapter.	No.	
LED Indicators				
Zone Thermostat Call Status	Yes.	No.	No.	
Equipment Call Status	Yes.	Yes.	Yes.	
Zoning Panel Status	Yes.	Yes.	Yes.	
Damper Position	Yes.	Yes.	Yes.	